

## HIGHLIGHTS

- Rotax<sup>®</sup> V-Twin engine
- Arched double A-arm front suspension with front sway bar
- Torsional Trailing-Arm Independent (TTI) rear suspension
- Front and rear FOX<sup>†</sup> 1.5 PODIUM<sup>†</sup> shocks
- Intelligent Throttle Control (iTC<sup>™</sup>) with riding modes
- 30 in. ITP<sup>†</sup> Cryptid<sup>†</sup> tires
- 14 in. cast-aluminum wheels
- Tri-Mode Dynamic Power Steering (DPS™)
- · Visco-Lok<sup>†</sup> QE auto-locking front differential
- · Relocated radiator
- 3,500 lb (1,588 kg) winch
- · Heavy-duty front and rear bumpers
- Mud-riding footrests
- 59 in. wheelbase
- Multifunction digital gauge
- X-package coloration, graphics and seat cover

Mudguards

#### SPECIFIC TO VISCO-4LOK PACKAGE

- NEW Visco-4Lok front differential
- Full wrap handguards

ENGINE	1000R with Visco-4Lok	1000R
Туре	91 hp, Rotax 976 cc V-twin, snorkeled, liquid cooled with relocated radiator	
Fuel Delivery System	Intelligent Throt with Electronic F	tle Control (iTC) uel Injection (EFI)
Transmission	CVT, P/R/N/H/extra-low L, standard engine braking	
Drive Train	Selectable 2WD/4WD/ Lock 4WD with Visco-4Lok front differential	Selectable 2WD/4WD with Visco-Lok QE auto- locking front differential
Power Steering	Tri-Mode Dynamic P	ower Steering (DPS)
SUSPENSIONS		
Front Suspension	Arched double A-arm with front sway bar	
Front Shocks	FOX 1.5 PODIUM	

i ioni odoponoloni	FOX 1.5 PODIUM Torsional Trailing-Arm Independent (TTI)	
Front Shocks		
Rear Suspension		
Rear Shocks	FOX 1.5 PODIUM	

### TIRES & WHEELS

ITP Cryptid 30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)
ITP Cryptid 30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)
14 in. cast aluminum

#### BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers	
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper	



Neo Yellow & Black / 1000R (with Visco-4Lok)

Granite Gray, Black & Manta Green / 1000R

DIMENSIONS & CAPACITIES	1000R with Visco-4Lok	1000R
Estimated Dry Weight*	1,014 lb (460 kg)	
LxWxH	97 x 50 x 51.5 in. (246 x 127 x 131 cm)	
Wheelbase	59 in. (149.9 cm)	
Ground Clearance	13 in. (33 cm)	
Seat Height	36.75 in. (93.3 cm)	
Rack Capacity	Rear: 200 lb (90 kg)	
Storage Capacity	Rear: 5.7 gal (21.4 L)	
Towing Capacity	1,650 lb (750 kg)	
Fuel Capacity	5.4 gal (20.5 L)	
Gauge	7.6 in. wide digital display: Speedometer, tachometer, odometer, trips and hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge, clock Lighter-type DC outlet in console,	
matumentation	standard connector in the back (15 A)	
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)	
Lighting	230 W from twin 60 W projectors and dual 55 W reflectors with tail light/brake light	
Winch	3,500 lb (1,588 kg) winch	
Seat	Standard	
Protection	Heavy-duty front & rear bumpers Full wrap handguards Mud-riding footrests Mudguards	Heavy-duty front and rear bumpers Mud-riding footrests Mudguards

# WARRANTY &

EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 36 months

© 2020 Bombardier Recreational Products Inc (BRP). All rights reserved. @, TM and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. 'Base model dry weight shown.'t Viso-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, since, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training ourse. For safety and training information, see your dealer or, in the U.S.A. all the ATV Safety Institute at 1-800-887-2887. In Canada, call the Canadian Safety Council at 1-613-739-1535, ext. 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding, alcohol and drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

