

2026 OUTLANDER MAX LIMITED



 Dusty Navy

PACKAGE HIGHLIGHTS

- 10.25 in. touchscreen display
- Specific CVT calibration
- High flow radiator cooling fan of 120W & 500 cm³
- Tri-Mode Dynamic Power Steering (DPS™)
- Smart-Shox™ technology
- Intelligent Engine Braking (iEB™) and driving modes
- Visco-4Lok[†] front differential
- 27 in. XPS Trail King 2 dedicated trail tires
- 14 in. aluminum wheels
- 4-disc brake system
- 3,500 lb winch with synthetic rope
- Full skid plate, front bumper, rear bumper
- Front sway bar
- Phone storage and USB charger
- Front drop-down storage
- Rear removable storage
- Special edition seat
- Extra painted panels
- LED signature lights

ENGINE	1000R
Type	101 hp / 69 lb-ft, Rotax® 999 cc V-twin, DOHC, liquid-cooled High flow radiator cooling fan of 120W & 500 cm³
Fuel Delivery System	Intelligent Throttle Control (ITC™) with Electronic Fuel Injection (EFI)
Transmission	pDrive primary CVT with specific calibration L / H / N / R / P
Drive Train	Selectable 2WD / 4WD / Lock 4WD with Visco-4Lok¹ front differential
Driving Assistance	Work / Standard / Sport modes Intelligent Engine Braking (IEB)
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Arched double A-arm with sway bar 10.8 in. (27.4 cm) travel
Front Shocks	KYB shocks with Smart-Shox Technology
Rear Suspension	Arched double A-arm 12 in. (30.5 cm) travel
Rear Shocks	KYB shocks with Smart-Shox Technology
TIRES & WHEELS	
Front / Rear Tires	XPS Trail King 2 – 27 x 8/10 x 14 in.
Wheels	14 in. aluminum
BRAKES	
Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm disc brakes with hydraulic twin-piston calipers

DIMENSIONS & CAPACITIES

Estimated Dry Weight*	998 lb (453 kg)
L x W x H	99 x 48.5 x 56.4 in. (252 x 123.2 x 143.2 cm)
Wheelbase	60.8 in. (154.4 cm)
Ground Clearance	12 in. (30.5 cm)
Seat Height	37.8 in. (96 cm)
Rack Capacity	Front: 120 lb (54.4 kg) Rear: 240 lb (109 kg)
Storage Capacity	10.6 gal (40 L)
Towing Capacity	1,830 lb (830 kg)
Fuel Capacity	5.1 gal (19.5 L)

FEATURES

Gauge	10.25 in. touchscreen display
Magneto	650 W
Instrumentation	Phone storage & USB-A charger
Ignition	RF Digitally Encoded Security System (D.E.S.S.™)
Lighting	LED headlights and taillights LED signature
Winch	Can-Am HD3500 (1,588 kg) winch with synthetic cable
Seat	Special Edition seat (color, stitching and material) with removable passenger seat
Handlebar	Standard
Protection	Full skid plate Heavy-duty front and rear bumpers
Hitch Type	2 in. hitch receiver

WARRANTY & EXTENDED SERVICE

Factory Warranty	1-year BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 48 months



© 2025 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at any time to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in the U.S.A. call the ATV Safety Institute at 1-800-887-2887. In Canada, call the Canadian Safety Council at 1-613-739-1535, ext 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding, alcohol and drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90 cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

